

円のピッチ指定(弧長)座標計算

		半径[右回り] =		与点間方向角 =		弧長ピッチ =	
		150.000		121° 27' 57"		4.000	
		X座標		Y座標		接線方向角	
		m		m		°	
登録No	点 名					弧 長	
						m	
始点	4 (B-R3)	-61 637.119	-71 673.186	101 32 24	0.000		
1	5060 (K-100)	-61 637.971	-71 669.278	103 4 4	4.000		
2	5061 (K-101)	-61 638.928	-71 665.394	104 35 44	8.000		
3	5062 (K-102)	-61 639.987	-71 661.537	106 7 25	12.000		
4	5063 (K-103)	-61 641.149	-71 657.710	107 39 5	16.000		
5	5064 (K-104)	-61 642.413	-71 653.915	109 10 46	20.000		
6	5065 (K-105)	-61 643.777	-71 650.155	110 42 26	24.000		
7	5066 (K-106)	-61 645.241	-71 646.432	112 14 6	28.000		
8	5067 (K-107)	-61 646.804	-71 642.750	113 45 47	32.000		
9	5068 (K-108)	-61 648.464	-71 639.111	115 17 27	36.000		
10	5069 (K-109)	-61 650.221	-71 635.518	116 49 8	40.000		
11	5070 (K-110)	-61 652.073	-71 631.973	118 20 48	44.000		
12	5071 (K-111)	-61 654.019	-71 628.478	119 52 28	48.000		
13	5072 (K-112)	-61 656.058	-71 625.037	121 24 9	52.000		
14	5073 (K-113)	-61 658.187	-71 621.651	122 55 49	56.000		
15	5074 (K-114)	-61 660.406	-71 618.323	124 27 30	60.000		
16	5075 (K-115)	-61 662.713	-71 615.055	125 59 10	64.000		
17	5076 (K-116)	-61 665.106	-71 611.850	127 30 50	68.000		
18	5077 (K-117)	-61 667.584	-71 608.710	129 2 31	72.000		
19	5078 (K-118)	-61 670.145	-71 605.638	130 34 11	76.000		
20	5079 (K-119)	-61 672.786	-71 602.634	132 5 52	80.000		
21	5080 (K-120)	-61 675.507	-71 599.702	133 37 32	84.000		
22	5081 (K-121)	-61 678.305	-71 596.844	135 9 12	88.000		
23	5082 (K-122)	-61 681.179	-71 594.061	136 40 53	92.000		
24	5083 (K-123)	-61 684.125	-71 591.356	138 12 33	96.000		
25	5084 (K-124)	-61 687.142	-71 588.731	139 44 14	100.000		
26	5085 (K-125)	-61 690.229	-71 586.186	141 15 54	104.000		
終点	11 (B-R9)	-61 690.488	-71 585.979	141 23 30	104.332		